

## Kalcret BNX

**Brand:** Cannon

**Product Code:** 0013803044430-20D

**Availability:** 200

**Weight:** 25.00kg

**Dimensions:** 50.00cm x 30.00cm x 20.00cm

### **Short Description**

With KALCRET troweling compound, it is possible to protect horizontal, vertical, sloping, and curved surfaces. Safe overhead processing is also easily achievable.

Temperature: up to 400°C

### **Description**

KALCRET is a wear-resistant, high-performance concrete made of high-strength hard aggregates in an extremely strong cement matrix. The improved compound is matched to the specific requirements and provides maximum resistance to erosion and abrasion.

KALCRET is the leading cement-bonded hard aggregate compound on the market. KALCRET combines excellent wear protection properties with ease of use. The specific advantage of all compound materials is their flexibility in practice. Large surfaces can be coated quickly and reliably to restore plant availability rapidly.

KALCRET is suitable for lining plant components and pipe systems, including in environmental engineering applications such as air and water filtration plants, in waste incineration plants, in power plants, in plants that produce construction materials, in cement works, and in the steel industry

### **Specification**

Wear stress

|                       |   |
|-----------------------|---|
| bauxite hard material | B |
| Temperature range     |   |
| up to 400°C           | N |
| Processing method     |   |
| applied by trowelling | X |

## Product Gallery